



**nassli**  
LED LIGHTS

## LED DOWN LIGHT CRX24-5

### Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

### Feature:

The product used as pure light source , using LED technology human and environment friendly,no PB, Hg nor UV.  
High power saving fixture, no decay and color temperature shift.  
Can be dimmable (through direct control or via network).



## SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>83%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20 / IP44
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-CRX24-5-N100-10W-XXK-SMD-NS-IP20	W37.5 H114 Ø100	10	1200
NSL-CRX24-5-N100-10W-XXK-SMD-TD-XX-IP20	W37.5 H114 Ø100	10	1200