



nassli
LED LIGHTS

LED DOWN LIGHT BIZZA

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	142-156Lm/W
Power supply	Tridonic / Nassli
LED Type	Citizen
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DLT-200-50W-XXK-COB-TD-XX-IP20	W83 L230 Ø210	50	7100
NSL-DLT-200-50W-XXK-COB-NS-IP20	W83 L230 Ø210	50	7100
NSL-DLT-200-40W-XXK-COB-TD-XX-IP20	W83 L230 Ø210	40	5680
NSL-DLT-200-40W-XXK-COB-NS-IP20	W83 L230 Ø210	40	5680
NSL-DLT-200-30W-XXK-COB-TD-XX-IP20	W83 L230 Ø210	30	4260
NSL-DLT-200-30W-XXK-COB-NS-IP20	W83 L230 Ø210	30	4260