



nassli
LED LIGHTS

LED TUBE FRAME

Application:

It can be widely used for Trade Shows, Supermarkets, Schools, Hospitals, Factories, Car Parking, Airport, Corridor etc....

Feature:

LED ceiling light: The LED diffuser light is mounted directly on the ceiling for plaster ceiling mounting. The LED moisture-proof diffuser light is already completely wired for LED technology and does not have to be converted. Operating temperature -20°C to 65°C, low heat generation: Temperature heat sink >1h max. approx. 45°C Robust plastic housing and protection class IP65 prevent penetration of foreign bodies or dust as well as protection against water jets

SPECIFICATIONS

ITEM	DESCRIPTION
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Mounting	Ceiling, Wall mounting
IP Rating	IP65
Warranty	5 Years



Order code	Dimensions(mm)	LED SIZE	IP Rating
NSL-WP-LTU-2x150-IP65	L1567 x W125 x H85	T8-150	65
NSL-WP-LTU-1x150-IP65	L1567 x W95 x H85	T8-150	65
NSL-WP-LTU-2x120-IP65	L1267 x W125 x H85	T8-120	65
NSL-WP-LTU-1x120-IP65	L1267 x W95 x H85	T8-120	65
NSL-WP-LTU-2x60-IP65	L667 x W125 x H85	T8-60	65
NSL-WP-LTU-1x60-IP65	L667 x W95 x H85	T8-60	65