



nassli
LED LIGHTS

LED TRACK LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc.

Feature:

The most common form of track lighting still consists of straight pieces of track that are attached directly to the surface of the wall or ceiling. They come with a piece that connects to a ceiling outlet, special 90-degree pieces for making turns, couplers to join two straight pieces together, and a "dead end" to safely cap the track at its end, but there are also curved or wave track fixtures as well as ones that are suspended below the ceiling



SPECIFICATIONS

| ITEM | DESCRIPTION |
|----------------|-----------------------------------|
| Input Voltage | 220 - 240 V A C |
| Frequency | 50 / 60 Hz |
| Power factor | >95% |
| CCT | 2700k,3300k,4000k,5000k,6000k |
| CRI | >80% |
| LED Efficiency | 85-95Lm/W |
| Power supply | Tridonic / Nassli |
| LED Type | Citizen |
| Materials | Aluminum, PC, & Friendly material |
| Beam Angle | 10° / 25° |
| Life Time | >50,000 Hour |
| Operating Temp | -20°C to +55°C |
| Storage Temp | -40°C to +80°C |
| Certifications | CE, SELV and ISO |
| Mounting | Wall Mounted, Suspended |
| IP Rating | IP20 |
| Dimmable | On Request |
| Emergency | On Request |
| Warranty | 5 Years |

| Order code | Dimensions(mm) | Power(Watt) | Lumen |
|----------------------------------|----------------|-------------|-------|
| NSL-TL-134-T3-15W-XXK-TD-XX-IP20 | W49 L127 | 15 | 1425 |
| NSL-TL-134-T3-15W-XXK-NS-XX-IP20 | W49 L127 | 15 | 1425 |
| NSL-TL-134-T3-15W-XXK-PH-XX-IP20 | W49 L127 | 15 | 1425 |
| NSL-TL-134-T3-25W-XXK-TD-XX-IP20 | W49 L127 | 25 | 2375 |
| NSL-TL-134-T3-25W-XXK-NS-XX-IP20 | W49 L127 | 25 | 2375 |
| NSL-TL-134-T3-25W-XXK-PH-XX-IP20 | W49 L127 | 25 | 2375 |
| NSL-TL-134-T3-30W-XXK-TD-XX-IP20 | W49 L127 | 30 | 2850 |
| NSL-TL-134-T3-30W-XXK-NS-XX-IP20 | W49 L127 | 30 | 2850 |