



nassli
LED LIGHTS

LED TUBE

Application:

It can be used for Hotels, Government Buildings, offices, Residential Buildings (villas, palaces, apartment), School, college and University, Hospitals, Super Market.

Feature:

The product is used as a pure light source, using LED technology, human and environment friendly, no Pb, Hg, nor UV. It does not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC / 95 - 305 VAC
Frequency	50 / 60 Hz
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Nassli / LF / ZY
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounting, Surface, Suspended
IP Rating	IP20
Dimmable	N/A
Emergency	N/A
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LTUV2-60T8-11W-XXK-SMD-ZY-IP20	L667 x W125 x H85	11	1210
NSL-LTUV2-120T8-14W-XXK-SMD-ZY-IP20	L1267 x W125 x H85	14	1540
NSL-LTUV2-120T8-18W-XXK-SMD-ZY-IP20	L1267 x W125 x H85	18	1980
NSL-LTUV2-120T8-20W-XXK-SMD-LF-IP20	L1267 x W125 x H85	20	2200
NSL-LTUV2-120T8-20W-XXK-SMD-ZY-IP20	L1267 x W125 x H85	20	2200
NSL-LTUV1-120T8-22W-XXK-SMD-LF-IP20	L1267 x W125 x H85	22	2420
NSL-LTUV2-150T8-30W-XXK-SMD-ZY-IP20	L1567 x W125 x H85	30	3300